



GOOD FLEX™ AIR & WATER HOSE 300 PSI

APPLICATION:

An economical air and water hose, Good Flex is suitable for a wide range of industrial, construction and agricultural applications.

PACKAGING: Packaged on reels, max 3 pieces per reel

BRANDING: GOOD FLEX™ AIR / WATER HOSE

TEMPERATURE: -40° F to 190° F (-40 C to 88 C)

CONSTRUCTION:

Tube: Black EPDM synthetic rubber

Reinforcement: Spiral Synthetic Yarn



Cover: Red synthetic rubber

INCHES ID X OD	MM ID X OD	Max WP PSI	Max WP MPa	Reel Length Feet.	WEIGHT LB/FT
1/4 x 0.53	6.4 x 13.5	300	2.07	750	0.10
3/8 x 0.70	9.5 x 17.8	300	2.07	750	0.17
1/2 x 0.84	12.7 x 21.3	300	2.07	750	0.22
5/8 x 1.00	15.9 x 25.4	300	2.07	750	0.33
3/4 x 1.15	19.1 x 29.2	300	2.07	600	0.37
1 x 1.48	25.4 x 37.3	300	2.07	500	0.58

Goodyear Rubber Products, Inc.
11301 47th Street N.
Clearwater, FL 33762 USA

International Phone: +1-727-822-4672
Toll Free in the USA: 1-800-FOR-HOSE
Email: Sales@GoodyearRubberProducts.com
Website: www.Goodflex.us



GOOD FLEX™ Water Suction & Discharge 150 PSI

APPLICATION:

Rubber Water Suction and Discharge hose for medium to heavy duty applications on either suction or discharge side of pumps

PACKAGING: Coiled and polywrapped

BRANDING: GOOD FLEX™ Water Suction & Discharge Hose
150 PSI

CONSTRUCTION:

Tube: Black synthetic rubber
Reinforcement: Spiral-plied fabrics and wire helix
Cover: Black synthetic rubber

TEMPERATURE: -25° F to 180° F (-32 C to 82 C)



INCHES ID X OD	MM ID X OD	WP PSI	Bend Radius in.	Vacuum in	WEIGHT LB/FT
1 x 1.348	25.4 x 34.2	150	3	29	0.42
1 1/2 x 1.852	38.1 x 47.0	150	5	29	0.64
2 x 2.352	50.8 x 59.7	150	5	29	0.83
2 1/2 x 2.893	63.5 x 73.5	150	6	29	1.09
3 x 3.436	76.2 x 87.3	150	8	29	1.19
4 x 4.447	101.6 x 112.9	150	10	29	2.05
6 x 6.613	152.4 x 168.0	150	12	29	4.91

Goodyear Rubber Products, Inc.
11301 47th Street N.
Clearwater, FL 33762 USA

International Phone: +1-727-822-4672
Toll Free in the USA: 1-800-FOR-HOSE
Email: Sales@GoodyearRubberProducts.com
Website: www.Goodflex.us



GOOD FLEX™ Petroleum Tank Truck Hose 150 PSI

APPLICATION:

For use in tank truck and in-plant operations to transfer gasoline, oil ethanol blends and other petroleum based products up to 50% aromatics. Designed for gravity flow or full suction service.

PACKAGING: Coiled and polywrapped

BRANDING: GOOD FLEX™ Petroleum Tank Truck 150 PSI

TEMPERATURE:

-25° F to 180° F (-32 C to 82 C)

CONSTRUCTION:

Tube: Black Nitrile synthetic rubber

Reinforcement: Multiple fabric plies with wire helix

Cover: Black SBR



INCHES ID X OD	MM ID X OD	WP PSI	Bend Radius in.	Vacuum in	WEIGHT LB/FT
1 x 1 7/16	25.34 x 36.62	150	2	29	0.55
1 1/4 x 1 45/64	32.00 x 43.38	150	3	29	0.7
1 1/2 x 1 31/32	38.00 x 50.06	150	4	29	0.86
2 x 2 31/64	51.16 x 63.26	150	5	29	1.14
2 1/2 x 3 1/32	63.69 x 77.06	150	6	29	1.57
3 x 3 17/32	76.14 x 89.51	150	7	29	1.84
4 x 4 19/32	102.13 x 116.55	150	10	29	2.61

Goodyear Rubber Products, Inc.
11301 47th Street N
Clearwater FL 33762 USA

International Phone: +1-727-822-4672
Toll Free in the USA: 1-800-FOR-HOSE
Email: Sales@GoodyearRubberProducts.com
Website: www.Goodflex.us



GOOD FLEX™ Plaster Grout & Concrete Hose

APPLICATION:

PGC hose for use in plaster, grout and shotcrete applications, handling a multitude of materials being pumped to concrete structures, dams, tunnel faces, swimming pools, etc. Meets ASME B30.27-2009 2:1 WP to Burst Ratio

PACKAGING: 50 ft. lengths coiled and polywrapped

BRANDING: GOOD FLEX™ Plaster Grout & Concrete Hose 1233 PSI (85 bar) WP Made in Canada

TEMPERATURE: -25° F to 180° F (-32 C to 82 C)

CONSTRUCTION:

Tube: Black synthetic rubber

Reinforcement: Spiral-plied high strength fabric

Cover: Black SBR rubber



INCHES ID X OD	MM ID X OD	WP PSI	WEIGHT LB/FT		
1 1/2 x 2.13	38.0 x 53.7	1233	.87		
2 x 2.69	51.2 x 67.1	1233	1.13		
2 1/2 x 3.25	63.4 x 82.3	1233	1.59		

Goodyear Rubber Products, Inc.
11301 47th Street N
Clearwater FL 33762 USA

International Phone: +1-727-822-4672
Toll Free in the USA: 1-800-FOR-HOSE
Email: Sales@GoodyearRubberProducts.com
Website: www.Goodflex.us



GOOD FLEX™ PRESSURE WASHER HOSE 4000 PSI

APPLICATION:

Economical high-pressure washer hose, Good Flex™ is suitable for working pressures up to 4000 PSI.

CONSTRUCTION:

- Tube:** Black NBR rubber
- Reinforcement:** Single Braid Steel Wire
- Cover:** Blue Synthetic Rubber

PACKAGING: Bulk in 50 ft. increments and assemblies*

BRANDING: GOOD FLEX™ PRESSURE WASHER HOSE

TEMPERATURE: -20° F to +250° F (-29° C to +121° C)

NOT RECOMMENDED FOR STEAM SERVICE!

MADE IN THE U.S.A.



Hose Size	ID (inches) Tolerance	OD (inches) Tolerance	Max WP PSI	Burst Pressure PSI	Weight lb/ft
3/8	.366-.398	.630-.669	4000	12000	0.205

*Our Hose assemblies can be supplied with or without quick couplings, wands and nozzles. Kink guards are standard on assemblies.

Goodyear Rubber Products, Inc.
11301 47th Street N
Clearwater, FL 33762 USA

International Phone: +1-727-822-4672
Toll Free in the USA: 1-800-FOR-HOSE

Email: Sales@GoodyearRubberProducts.com
Website: www.GoodyearRubberProducts.com
www.Goodflex.us



GOOD FLEX™ Purple Reclaimed Water Hose

APPLICATION:

A high quality general purpose water hose color coded in purple to identify for use with reclaimed water in both municipal and residential use.

PACKAGING: Packaged on reels, max 3 pieces per reel

BRANDING: GOOD FLEX™ 3/4" I.D. 150 PSI CAUTION - RECYCLED/ RECLAIMED WATER- DO NOT DRINK / NO BEBER

TEMPERATURE: -10° F to 158° F (-23 C to 70 C)

CONSTRUCTION:

Tube: Black Thermoplastic Compound

Reinforcement: Spiral Synthetic Yarn

Cover: Pantone Purple Smooth Thermoplastic



INCHES ID X OD	MM ID X OD	Max WP PSI	Max WP MPa	Reel Length Feet.	WEIGHT LB/FT
3/4 x 1.11	19.1 x 28.2	150	1.72	450	0.28

Goodyear Rubber Products, Inc.
11301 47th Street N.
Clearwater FL 33762 USA

International Phone: +1-727-822-4672
Toll Free in the USA: 1-800-FOR-HOSE
Email: Sales@GoodyearRubberProducts.com
Website: www.Goodflex.us