

The Best Hose Suspension in the World



MODEL
HB 100 ED
For
Hose I.D. 1" (2.5cm)



Material:	URETHANE
Length:	16 inches / 40.64 centimeters
Shipping Weight:	3 pounds / 1.4 kilograms
Shipping Dimensions:	21x8x4" / 50.8x21x7.5cm
*Sling height: *Measured from top of the bun to the top of the sling	6 inches / 15.24 centimeters
Sling type:	"D-RING" (RS 16 D)
Sling material:	UV Resistant Treated Nylon
Rated capacity:	800 lbs @ 5-1 Safety Factor
Maximum temperature:	200 degrees F / 93.3 Celsius

Notes: The most popular petroleum hose model.
Used throughout the world at refueling stations.
Often used conjunction with retractors.

The Best Hose Suspension in the World



MODEL
HB 125 ED
For
Hose I.D. 1 1/4" (3.1cm)



Material:	URETHANE
Length:	17.50 inches / 44.45 centimeters
Shipping Weight:	3.25 pounds / 1.48 kilograms
Shipping Dimensions:	21x8x4" / 50.8x21x7.5cm
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	5.75 inches / 14.6 centimeters
Sling type:	"D-RING" (RS 16 D)
Sling material:	UV Resistant Treated Nylon
Rated capacity:	800 lbs @ 5-1 Safety Factor
Maximum temperature:	200 degrees F / 93.3 Celsius

Notes: Used with petroleum hose, refueling stations with hohose retractors, hydraulic hose bundles and theatrical cabling.

The Best Hose Suspension in the World



MODEL
HB 150 ED
For
Hose I.D. 1 1/2" (3.8cm)



Material:	URETHANE
Length:	19.50 inches / 45.09 centimeters
Shipping Weight:	3.75 pounds / 1.71 kilograms
Shipping Dimensions:	21x8x4" / 50.8x21x7.5cm
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	4.50 inches / 11.43 centimeters
Sling type:	"D-RING" (RS 16 D)
Sling material:	UV Resistant Treated Nylon
Rated capacity:	800 lbs @ 5-1 Safety Factor
Maximum temperature:	200 degrees F / 93.3 Celsius

Notes: Often used for bundled hoses/cable like theatrical cable for lighting and sound.

The Best Hose Suspension in the World



MODEL
HB 200 ED
For
Hose I.D. 2" (5cm)



Material:	URETHANE
Length:	18 inches / 45.72 centimeters
Shipping Weight:	4 pounds / 1.81 kilograms
Shipping Dimensions:	21x8x4" / 50.8x21x7.5cm
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	7.25 inches / 18.42 centimeters
Sling type:	"D-RING" (RS 200 D)
Sling material:	UV Resistant Treated Nylon
Rated capacity:	800 lbs @ 5-1 Safety Factor
Maximum temperature:	200 degrees F / 93.3 Celsius

Notes: Available with Type 4 Hook Eye (RS 200H)

The Best Hose Suspension in the World



MODEL
HB 200 SRD
For
Hose I.D. 2" (5cm)



Material:	URETHANE
Length:	12 inches / 30.48 centimeters
Shipping Weight:	2.5 pounds / 1.14 kilograms
Shipping Dimensions:	13x5x3.5" / 33.5x13.5x9cm
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	9.60 inches / 24.38 centimeters
Sling type:	"D-RING" (RS 200 D)
Sling material:	UV Resistant Treated Nylon
Rated capacity:	800 lbs @ 5-1 Safety Factor
Maximum temperature:	200 degrees F / 93.3 Celsius

Notes: Available with Type 4 Hook Eye (RS 200H)

The Best Hose Suspension in the World



MODEL
HB 300 D
For
Hose I.D. 3" (8.0cm)



Material:	URETHANE
Length:	12.75 inches / 32.39 centimeters
Shipping Weight:	4.25 pounds / 1.93 kilograms
Shipping Dimensions:	13.5x5.5x5" / 35x14x12cm
Sling height: <small> Measured from top of the bun to the top of the sling</small>	8.50 inches / 21.60 centimeters
Sling type:	"D-RING" (RS 300 D)
Sling material:	UV Resistant Treated Nylon
Rated capacity:	800 lbs @ 5-1 Safety Factor
Maximum temperature:	200 degrees F / 93.3 Celsius

Notes: Light duty bun,
Easier mounting with the "D-Ring" attachment.

The Best Hose Suspension in the World



MODEL
HB 300 H
 For
Hose I.D. 3" (8.0cm)



Material:	URETHANE
Length:	12.75 inches / 32.39 centimeters
Shipping Weight:	4.25 pounds / 2.28 kilograms
Shipping Dimensions:	13.5x5.5x5" / 35x14x12cm
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	14.75 inches / 37.70 centimeters
Sling Type:	Type 4 Hook Eye (RS 300H)
Sling Material:	UV Resistant Treated Nylon
Rated Capacity:	1500 lbs @ 5-1 safety factor
Maximum Temperature:	200 degrees F / 93.3 Celsius

Notes: 300 H Light duty bun with type 4 hook eye sling for increased strength and work safety.

The Best Hose Suspension in the World



MODEL
HB 400 D
For
Hose I.D. 4" (10.0cm)



Material:	URETHANE
Length:	11.5 inches / 21.22 centimeters
Shipping Weight:	5 pounds / 2.28 kilograms
Shipping Dimensions:	13x7.5x6.5" / 33x19x16.5cm
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	8 inches / 20.00 centimeters
Sling type:	"D-RING" (RS 400 D)
Sling material:	UV Resistant Treated Nylon
Rated capacity:	800 lbs @ 5-1 Safety Factor
Maximum temperature:	200 degrees F / 93.3 Celsius

Notes: Light duty bun, easier mounting with the "D-Ring" attachment. Often used to support tanker

The Best Hose Suspension in the World



MODEL
HB 400 H
For
Hose I.D. 4" (10.0cm)



Material:	URETHANE
Length:	11.5 inches / 29.21 centimeters
Shipping Weight:	5 pounds / 2.28 kilograms
Shipping Dimensions:	22.5x9x15" / 57x23x30.5 cm
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	16.0 inches / 40.64 centimeters
Sling Type:	Type 4 Hook Eye (RS 400H)
Sling Material:	UV Resistant Treated Nylon
Rated Capacity:	1500 lbs @ 5-1 safety factor
Maximum Temperature:	200 degrees F / 93.3 Celsius

Notes: 400 H Light duty bun with type 4 hook eye sling for increased strength and work safety.

The Best Hose Suspension in the World



MODEL
HB 600 H
For
Hose I.D. 6" (15cm)



Material:	URETHANE
Length:	21.5 inches / 54.6 centimeters
Shipping Weight:	16 pounds / 7.28 kilograms
Shipping Dimensions:	22.5x9x15" / 57x23x30.5 cm
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	22.5 inches / 57.15 centimeters
Sling Type:	Type 4 Hook Eye (RS 600H)
Sling Material:	UV Resistant Treated Nylon
Rated Capacity:	8000 lbs @ 5-1 safety factor
Maximum Temperature:	200 degrees F / 93.3 Celsius

Notes: Use Heat Wrap Model HW 600 to extend temperature capacity up to 1100 degrees Fahrenheit (593 Celsius).

The Best Hose Suspension in the World



MODEL
HB 800 H
 For
Hose I.D. 8" (20.0cm)



Material:	URETHANE
Length:	30.5 inches / 77.47 centimeters
Shipping Weight:	35 pounds / 15.92 kilograms
Shipping Dimensions:	31.25x12x15" / 80x30.5x38cm
*Sling height: *Measured from top of the bun to the top of the sling	18 inches / 45.72 centimeters
Sling Type:	Type 4 Hook Eye (RS 800H)
Sling Material:	UV Resistant Treated Nylon
Rated Capacity:	12000 lbs @ 5-1 safety factor
Maximum Temperature:	200 degrees F / 93.3 Celsius

Notes: Use Heat Wrap Model HW 800 to extend temperature capacity up to 1100 degrees Fahrenheit (593 Celsius).

The Best Hose Suspension in the World



MODEL
HB 1000 H
 For
Hose I.D. 10" (25.0cm)




Material:	URETHANE
Length:	40.75 inches / 103.51 centimeters
Shipping Weight:	60 pounds / 27.20 kilograms
Shipping Dimensions:	42x14x18" / 105x34x46cm
*Sling height: *Measured from top of the bun to the top of the sling	19.25 inches / 48.90 centimeters
Sling Type:	Type 4 Hook Eye (RS 1000H)
Sling Material:	UV Resistant Treated Nylon
Rated Capacity:	15000 lbs @ 5-1 safety factor
Maximum Temperature:	200 degrees F / 93.3 Celsius

Notes: Use Heat Wrap Model HW 1000 to extend temperature capacity up to 1100 degrees Fahrenheit (593 Celsius).

The Best Hose Suspension in the World



MODEL
HB 1200 H
 For
Hose I.D. 12" (30.0cm)



Material:	URETHANE
Length:	40.75 inches / 103.51 centimeters
Shipping Weight:	62 pounds / 28.20 kilograms
Shipping Dimensions:	42x14x18" / 105x34x46cm
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	23.25 inches / 59.06 centimeters
Sling Type:	Type 4 Hook Eye (RS 1200H)
Sling Material:	UV Resistant Treated Nylon
Rated Capacity:	15000 lbs @ 5-1 safety factor
Maximum Temperature:	200 degrees F / 93.3 Celsius

Notes: Same Mold as HB 1000H but with longer sling to accommodate 12" I.D Hose.

The Best Hose Suspension in the World



HOSECADDY™

MODEL
HC 1000



Material:	Each Hosecaddy™ is made with a rugged steel construction that then undergoes hot dipped galvanization and powder coating to ensure years of maintenance-free protection performance.
Weight:	The hose caddy at 93lbs (42.2 kg) is lightweight and durable.
Dimensions:	45" long x 20 1/4" wide x 25" high.
Load Capacity	Easy rolling heavy duty 6" swivel castors on all four corners have a working load capacity of 1600 lbs.
Hose Dimensions	Designed for 6" through 12" large bore hose or a bundle of small 3-4" hoses.

- Notes:**
- Designed to tip sideways for easy loading and unloading of the hose.
 - Available in different colors

The Best Hose Suspension in the World



HOSE HORSE™

MODEL
HH



Material:	Molded Plastic
Weight:	From 4 - 18 lbs (depends on model)
Dimensions:	Depends on Model
Hose Dimensions	Models available to fit hose sizes from 2 inch up to 24 inches.

*** * *GET YOUR HOSE OFF THE GROUND* * ***

STACKABLE

DURABLE

AFFORDABLE