

## Pressure Washer and Cleaning Hose

Jobs get messy. That's when you need Continental's pressure washer and cleaning hose. Our hoses can withstand pressures up to 6000 psi as well as a wide range of temperatures (between -20°F to 325°F). No matter what you have to clean up, Continental has a hose that will become your cleanup chore champion.



# Neptune 1500

1500 psi WP



### Application

For pressure washer equipment, agricultural sprayers and high-pressure air lines.

### Construction

› **Tube**

Nitrile synthetic rubber

› **Cover**

Blue, Gray or Yellow oil-resistant synthetic rubber, RMA Class B (Medium Oil Resistance)

› **Reinforcement**

One braided synthetic yarn up through 1/2"  
Two braided synthetic yarn for 3/4"

### Temperature Range

-20°F to 210°F (-29°C to 99°C)

### Neptune 1500

Part #	Hose Color	Hose ID	Packaging	Length	Material #
		in.		ft.	
20449806	Blue	1/4	MXMS w/ Kink Guards	25	536-374
20142362	Blue	3/8	MXMS w/ Kink Guards	50	536-374
20590578	Blue	1/2	MXMS w/ Kink Guards	75	536-374
20023093	Gray	1/4	MXMS w/ Kink Guards	25	536-387
20023096	Gray	3/8	MXMS w/ Kink Guards	50	536-387
20023099	Gray	1/2	MXMS w/ Kink Guards	75	536-387
20023102	Gray	1/4	MXMS w/ Kink Guards	100	536-388
20023106	Blue	5/16	MXMS w/ Kink Guards	25	536-388
20023109	Blue	3/8	MXMS w/ Kink Guards	50	536-388
20023116	Blue	1/2	MXMS w/ Kink Guards	75	536-388
20029580	Yellow	3/8	MXMS w/ Kink Guards	100	536-490

# Neptune 3000

3000 psi WP



### Application

For use on pressure washer machines with working pressures up to 3000 psi. Rated to temperatures of -20°F to 250°F (-29°C to 121°C).

### Construction

› **Tube**

Nitrile synthetic rubber

› **Cover**

Black, Blue, Yellow or Gray oil-resistant synthetic rubber, RMA Class B (Medium Oil Resistance)

› **Reinforcement**

One braided steel wire

### Temperature Range

-20°F to 250°F (-29°C to 121°C)

### Neptune 3000

Part #	Hose Color	Hose ID	Packaging	Length	Material #
		in.		ft.	
20023506	Black	1/4	MXMS w/ Kink Guards	25	539-085
20023518	Black	3/8	MXMS w/ Kink Guards	50	539-085
20023613	Black	1/2	MXMS w/ Kink Guards	100	539-085
20023623	Blue	1/4	MXMS w/ Kink Guards	25	539-089
20023638	Blue	3/8	MXMS w/ Kink Guards	50	539-089
20023670	Blue	1/2	MXMS w/ Kink Guards	100	539-089
20023720	Gray	1/4	MXMS w/ Kink Guards	25	539-090
20023726	Gray	3/8	MXMS w/ Kink Guards	50	539-090
20216243	Gray	1/2	MXMS w/ Kink Guards	100	539-090
20155405	Yellow	1/4	MXMS w/ Kink Guards	25	539-104
20023949	Yellow	3/8	MXMS w/ Kink Guards	50	539-104
20023959	Yellow	1/2	MXMS w/ Kink Guards	100	539-104

## Neptune 4500

4500 psi WP



### Application

For use on pressure washer machines with working pressures up to 4500 psi.

### Construction

#### › Tube

Nitrile synthetic rubber

#### › Cover

Smooth finish black or blue oil-resistant synthetic rubber, ARPM Class B (Medium Oil Resistance)

#### › Reinforcement

One braided steel wire

### Temperature Range

-20°F to 250°F (-29°C to 121°C)

### Neptune 4500

Part #	Hose Color	Hose ID	Packaging	Length	Material #
		in.		ft.	
20069357	Blue	1/4	MXMS w/ Kink Guards	100	539-124
20024005	Blue	3/8	MXMS w/ Kink Guards	100	539-124
20023741	Black	3/8	MXMS w/ Kink Guards	100	539-091
20023757	Black	1/2	MXMS w/ Kink Guards	100	539-091

## Neptune 6000

6000 psi WP



### Application

For use on pressure washer machines with working pressures up to 6000 psi.

### Construction

#### › Tube

Nitrile synthetic rubber

#### › Cover

Wrapped finish black oil-resistant synthetic rubber, ARPM Class B (Medium Oil Resistance)

#### › Reinforcement

Two braided steel wires

### Temperature Range

-20°F to 250°F (-29°C to 121°C)

### Neptune 6000

Part #	Hose Color	Hose ID	Packaging	Length	Material #
		in.		ft.	
20551519	Gray	3/8	MXMS w/ Kink Guards	100	539-148
20046112	Black	3/8	MXMS w/ Kink Guards	100	539-149